

A tough multi-purpose printer



MN-4203

‘Compact Desktop Barcode Printer’

MN-4203

- Compact & easy to use
- Durable & reliable
- Ideal for office, medical, retail & shipping use
- International language print capabilities

MN-4203

General Specifications:

Model	MN-4203	
Print Method	Thermal Direct / Thermal Transfer (Option)	
Print Resolution	203 dpi (8 dot / mm)	
Print Area	Max Width 102mm x Length 584mm (Width 4.01" x Length 23.0")	
Print Speed	Max 76mm/sec (3"/sec)	
Media Type	Roll-fed, Fan-fold, Die-cut, Continuous, Perforated Label and Tag / Ticket media	
Media Size	Width	25.4mm - 109mm (1.0" - 4.3")
	Length	584mm (0.23")
	Other	Max roll outer diameter 102mm (4"), Wound Face Out
Ribbon	Width	Max 110mm (4.33")
	Length	Max 110mm
	Other	Core Inner Diameter 13mm, Wound Face In
Sensor Type	Reflective Sensor for Pre-printed sensor mark (Fixed),	
	Transmissive sensor for die-cut media (Fixed)	
Interface	Parallel : Centronics	
	Serial : RS232 at 300 to 38400 bps	
	USB : Version 1.1	
Barcode Symbologies	Code 39, Interleaved 2 of 5, Code 128, Codabar, UPC-A, UPC-E, UPC/EAN 2 and 5 digit addendums,	
	EAN-8, EAN-13, Code 93, UCC/EAN Code 128, Postnet, PDF417, UPS MaxiCode	
Matrix Fonts	Expansion	All fonts expandable vertically and horizontally up to 24x
	Rotation	0°, 90°, 180°, 270°
Dimensions	H 152mm x W 216mm x D 241mm (H 6.0" x W 8.5" x D 9.5")	
Weight	2.4kg (5.2lb)	
Power	115VAC, 230VAC, 50/60Hz	
Environment	Operating : 4 - 35°C (10 - 95% RH, non-condensing)	
Options	Thermal Transfer Kit, Present Sensor, Cutter, 3MB Flash card, External media supply	

SATO AUSTRALIA Pty Ltd.
P.O. Box 1364,
Glen Waverley, Victoria, 3150
Melbourne, Australia
email : sales@satoaustralia.com
Phone Toll Free : 1800 624 654

SATO NEW ZEALAND Ltd.
P.O. Box 305-031,
North Shore, Auckland
New Zealand
email : sales@satonewzealand.com
Phone Toll Free : 0800 784 578